

# 3316-1

## 1/16" BLACK POLYETHYLENE SINGLE COATED FOAM TAPE

### PRODUCT DESCRIPTION


#### Single Coated Tape with Liner

3316-1 is a 1/16" thick black closed cell, crosslinked polyethylene foam coated on one side with a high performance acrylic based adhesive with a white kraft liner.

### FEATURES & BENEFITS

- Easily die cut
- Low application temperature
- Great chemical resistance
- Low compression set
- Better conformability, cushioning & vibration damping

### PRODUCT CONSTRUCTION



### PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness (Total)	64.90 mils	1.648 mm	PSTC-133
Adhesive Thickness	2.40 mils	0.061 mm	PSTC-133
Carrier Thickness	62.50 mils	1.588 mm	PSTC-133
Peel Adhesion	75 oz/in	20.84 N/25mm	PSTC-101
Tack	28 oz	794 g	ASTM D 2979
Shear Adhesion	>168 hrs @ 2.2 psi	>168 hrs @15.2 kPa	PSTC-107
Tensile Strength	114 lb/in	12 N/25mm	PSTC-131
Elongation	269 %	269 %	
Minimum Service Temperature	10 °F	-12 °C	
Maximum Service Temperature	180 °F	82 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

### Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street  
Easthampton, MA 01027

413-527-7120 Main  
800-356-3572 Toll Free U.S.

[www.adhesiveapps.com](http://www.adhesiveapps.com)

**Adhesive**  
Applications™

Rev A

7/24/2018

