

7008B

1/8" WHITE POLYETHYLENE DOUBLE COATED FOAM TAPE

PRODUCT DESCRIPTION

Double Coated Tape

7008B is a 1/8" thick white closed cell, crosslinked polyethylene foam coated on both sides with a high performance acrylic based adhesive with a 4 mil blue poly liner.

FEATURES & BENEFITS

- Easily die cut
- Low application temperature
- Great chemical resistance
- Low compression set
- Best conformability, cushioning. & vibration damping

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness (Total)	129.00 mils	3.277 mm	PSTC-133
Adhesive Thickness (Liner Side)	2.00 mils	0.051 mm	PSTC-133
Carrier Thickness	125.00 mils	3.175 mm	PSTC-133
Adhesive Thickness (Exposed Side)	2.00 mils	0.051 mm	PSTC-133
Peel Adhesion	80 oz/in	22.23 N/25mm	PSTC-101
Tack	33 oz	936 g	ASTM D 2979
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @15.2 kPa	PSTC-107
Tensile Strength	195 lb/in	854 N/25mm	PSTC-131
Elongation	230 %	230 %	
Minimum Service Temperature	10 °F	-12 °C	
Maximum Service Temperature	180 °F	82 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

Rev A

7/24/2018

