

PBA0830-1

1/8" BLACK POLYETHYLENE SINGLE COATED DUCT GASKET TAPE

PRODUCT DESCRIPTION


Single Coated Tape with Liner

PBA0830-1 is a 1/8" thick black closed cell, crosslinked polyethylene foam coated on one side with a high performance acrylic based adhesive with a white kraft liner.

FEATURES & BENEFITS

- Easily die cut
- Low application
- Great chemical resistance
- Low compression set
- Best conformability, cushioning, & vibration damping

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness (Total)	126.80 mils	3.221 mm	PSTC-133
Adhesive Thickness	1.80 mils	0.046 mm	PSTC-133
Carrier Thickness	125.00 mils	3.175 mm	PSTC-133
Peel Adhesion	65 oz/in	18.06 N/25mm	PSTC-101
Tack	21 oz	595 g	ASTM D 2979
Shear Adhesion	>24 hrs @ 2.2 psi	>24 hrs @15.2 kPa	PSTC-107
Tensile Strength	240 lb/in	26 N/25mm	PSTC-131
Elongation	210 %	210 %	
Minimum Service Temperature	10 °F	-12 °C	
Maximum Service Temperature	176 °F	80 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

Rev A

7/24/2018

