

S5513

POLYSIL YELLOW SILICONE ADHESIVE TAPE

PRODUCT DESCRIPTION

Single Coated Tape

PolySil™ S5513 is a yellow high tack polyester (PET) tape with controlled adhesion and good conformability. The controlled level of crosslinking assures a proper balance of adhesion to substrates and chemical and temperature resistance.

FEATURES & BENEFITS

- High tack for quick adhesion
- Clean removal / no adhesive residue
- Chemical and abrasion resistant
- Good conformability

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Product Thickness (Total)	3.60 mils	0.091 mm	PSTC-133
Adhesive Thickness	2.60 mils	0.066 mm	PSTC-133
Carrier Thickness	1.00 mils	0.025 mm	PSTC-133
Peel Adhesion	40 oz/in	11.11 N/25mm	PSTC-101
Tack	40 oz	1134 g	ASTM D 2979
Shear Adhesion	168 hrs @ 2.2 psi	168 hrs @15.2 kPa	PSTC-107
Tensile Strength	25 lb/in	3 N/25mm	PSTC-131
Elongation	180 %	180 %	
Minimum Service Temperature	-60 °F	-51 °C	
Maximum Service Temperature	350 °F	177 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

Rev C

07/24/2018

