

055

Double-Coated Polyester

Other ITC data sheets are available on our website adhesiveapps.com/our-products

Description:	Double-Coated Polyester
Substrate:	.5 mil clear polyester
Adhesive:	Synthetic rubber
Tape Thickness (Mils):	3
Tape Color:	Clear
Release Liner:	53# 3 mil white paper
Print Color:	None
Print Text:	None
Adhesion (Oz/In Width): Tensile	Liner Side=80, Exposed Side=10
Strength (Lbs/In Width):	10
Elongation (% at Break):	50
Minimum Temperature (°F):	0
Maximum Temperature (°F):	150
Surface Preparation:	Surface should be clean, dry, & free of oil
Shelf Life:	1 year when stored in original packaging at 70°F and 50% relative humidity

Common Uses

- Temporary laminating, mounting, & attaching

Configurations Available

- Master rolls
- Logs
- Slit rolls, hand & machine-length
- Traverse-wound spools

Similar Products

- Need high tack on the exposed side? • Consider ITC# 550.

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

