

1210L

High Bond D/C Polypropylene - 53# Paper Liner

Other ITC data sheets are available on our website adhesiveapps.com/our-products

DESCRIPTION

Product 1210L is a double coated clear polypropylene film tape which is manufactured on a 53 lb. paper release liner. Product 1210L is double coated with a proprietary clear adhesive system which exhibits outstanding bond strength to difficult surfaces, such as untreated polyethylene film and other synthetics. It's extremely high shear adhesive characteristics make this product very effective for vertical bonding applications.

SUGGESTED USES

Product 1210L can be used as a permanent closure method for polyethylene and polypropylene copolymer bags where the closure cannot be reopened without the bag being destroyed. Product 1210L is recommended for use on polybags with a gauge up to .003", and is available on an extended poly liner for hot bar cutting (ITC#1510XL).

SPECIFICATIONS

BACKING:	clear polypropylene film; .0012"		
ADHESIVE:	clear synthetic copolymer-high tack permanent type		
LINER:	53# 3.2 mil white polysilicone paper		
THICKNESS, LINER (in.):	.0032	TENSILE STRENGTH (lb./in.):	22
THICKNESS, TAPE:	.0092	ELONGATION (%):	75
ADHESION (ozs./in. width):	180+	APPLICATION TEMP (F):	65-120
HOLDING POWER (min.):	10,000+	TEMPERATURE RANGE (F):	10-150
TACK (in.):	<1	EXTENDED LINER:	YES

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

