

# 210

## Double Coated Polypropylene Tape

Other ITC data sheets are available on our website [adhesiveapps.com/our-products](http://adhesiveapps.com/our-products)

### DESCRIPTION

**Product 210** is designed as a general-purpose double-coated polypropylene film tape. Based upon a 3/4 mil biaxially-oriented clear polypropylene film, **Product 210** exhibits good peel adhesion and high quickstick on both sides. The high density polysilicone liner allows easy removal from the aggressive pressure-sensitive adhesive system.

### SUGGESTED USES

**Product 210** is designed for a wide range of splicing, holding, joining, attaching, mounting, and laminating applications. Used for core start-ups and laminating and/or splicing of cork, felt, and paper. Can be torn with moderate ease by hand, or dispensed using most double-coated tape dispensers.

### SPECIFICATIONS

**BACKING:** polypropylene film, clear; .00075  
**ADHESIVE:** synthetic copolymer, permanent type  
**LINER:** 3.2 mil polysilicone type

<b>THICKNESS, LINER (in.):</b>	.0032	<b>TENSILE STRENGTH (lb./in.):</b>	22
<b>THICKNESS, TAPE (in.):</b>	.0032	<b>ELONGATION (%):</b>	75
<b>ADHESION (ozs./in width):</b>	90	<b>APPLICATION TEMP (F):</b>	60-120
<b>HOLDING POWER (min.):</b>	6000	<b>TEMPERATURE RANGE (F):</b>	-5 to +180
<b>TACK (in.)</b>	3	<b>LIFT EDGE AVAILABLE:</b>	NO

GOVERNMENT SPECIFICATION CONFORMANCE: UU-T-91E, Type I, Class I

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

## Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street  
Easthampton, MA 01027

413-527-7120 Main  
800-356-3572 Toll Free U.S.

[www.adhesiveapps.com](http://www.adhesiveapps.com)

**Adhesive**  
Applications™

