

219

Double Coated Cloth Tape

Other ITC data sheets are available on our website adhesiveapps.com/our-products

DESCRIPTION

Product 219 is a high strength, economy-grade, double coated cloth tape that is based on a durable synthetic cloth carrier with an aggressive pressure-sensitive adhesive system. This high performance, highly conformable product offers immediate quick stick, yet its dimensional stability allows for removability.

SUGGESTED USES

Product 219 is used for quick and easy tacking of carpet edges, and for carpet installing where removability from various surfaces such as wood or cement is required. Excellent for use on irregular surfaces for joining, mounting, and laminating where adhesion is desired. **Product 219** can also be used to mount printing plates, and is widely used to mount containment barriers during asbestos removal.

SPECIFICATIONS

BACKING: synthetic cloth
ADHESIVE: synthetic copolymer-pigmented-permanent
LINER: type 53# 3.2 mil white polysilicone paper

THICKNESS, LINER (in.):	.0032	TENSILE STRENGTH	23
THICKNESS, TAPE (in.):	.009	(lb./in.): ELONGATION (%):	10
ADHESION (ozs./lb. width):	65	APPLICATION TEMP (F):	35-120
HOLDING POWER (min):	3,000	TEMPERATURE RANGE (F):	30 to 140
TACK (in):	2	LIFT EDGE AVAILABLE:	NO

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

