

# 222

## Double Coated Polyethylene Tape

Other ITC data sheets are available on our website [adhesiveapps.com/our-products](http://adhesiveapps.com/our-products)

### DESCRIPTION

**Product 222** is a 3 mil permanent (non-removable) double-coated white polyethylene film tape with an exclusive synthetic rubber-based adhesive system and a 40 lb. super calendared release liner. **Product 222** is one of our most economical double-coated tapes.

### SUGGESTED USES

**Product 222** is recommended for carpet installation and a wide range of industrial applications involving laminating, splicing, and joining of different surfaces. Ideal where slightly more bulk is required in a film based tape. Conformability is excellent.

### SPECIFICATIONS

**BACKING:** polyethylene film, white; .0015"  
**ADHESIVE:** synthetic copolymer, permanent type  
**LINER:** 40 lb. super calendared type

<b>THICKNESS, LINER (in.):</b>	.0025	<b>TENSILE STRENGTH</b>	7
<b>THICKNESS, TAPE (in.):</b>	.004	<b>(lb./in.): ELONGATION (%):</b>	100
<b>ADHESION (ozs./in. width):</b>	50	<b>APPLICATION TEMP (F):</b>	60-120
<b>HOLDING POWER (min.):</b>	10,000	<b>TEMPERATURE RANGE (F):</b>	-5 to 140
<b>TACK (in.):</b>	3		

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

## Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street  
Easthampton, MA 01027

413-527-7120 Main  
800-356-3572 Toll Free U.S.

[www.adhesiveapps.com](http://www.adhesiveapps.com)

**Adhesive**  
Applications™

