

280

Double Coated Crepe Paper Tape

Other ITC data sheets are available on our website adhesiveapps.com/our-products

DESCRIPTION

Product 280 is comprised of a high quality saturated crepe paper stock double coated with a high tack, high shear synthetic rubber-based adhesive system. Adhesion is excellent to practically all surfaces, including fabric and synthetics. Product 280 exhibits excellent conformability and, with its super calendared release liner, can be die cut.

SUGGESTED USES

Product 280 possesses excellent tack and dead load shear properties, therefore it is recommended for applications where this tack is needed for bonding, laminating, or holding. Product 280 works well in joining irregular surfaces, and is also useful for holding wood cuts and dies. Also widely used in the printing industry for mounting rubber or plastic printing plates.

SPECIFICATIONS

BACKING: saturated crepe paper; .005"
ADHESIVE: synthetic copolymer, high tack, permanent type
LINER: 52# 3.2 mil white polysilicone paper

THICKNESS, LINER (in.):	.0032	TENSILE STRENGTH	21
THICKNESS, TAPE (in.):	.007	(lb./in.): ELONGATION (%):	7
ADHESION (ozs./in. width):	100	APPLICATION TEMP (F):	60-120
HOLDING POWER (min):	10,000	TEMPERATURE RANGE (F):	-5 to 180
TACK (in.):	1		

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

