

282

Double Coated Crepe Paper Tape

Other ITC data sheets are available on our website adhesiveapps.com/our-products

DESCRIPTION

Product 282 is comprised of a high quality saturated crepe paper stock double coated with a medium tack, high shear system. Adhesion is moderate to most surfaces, with excellent reposition ability characteristics. Product 282 exhibits superb tensile strength and conforms to most smooth dry surfaces without tearing.

SUGGESTED USES

Product 282 is excellent for mounting Golf Club handle grips. Product 282 possesses moderate tack and excellent dead load shear properties, therefore it is recommended for applications where some tack is needed for bonding, laminating, or holding, but later removability may be required.

SPECIFICATIONS

BACKING: saturated crepe paper; .004"
ADHESIVE: synthetic copolymer, moderate tack, permanent type
LINER: 52# 3.2 mil white polysilicone paper

THICKNESS, LINER (in.):	.0032	TENSILE STRENGTH	21
THICKNESS, TAPE (in.):	.0055	(lb./in.): ELONGATION (%):	7
ADHESION (ozs./in. width):	50	APPLICATION TEMP (F):	60-120
HOLDING POWER (min.):	5,000	TEMPERATURE RANGE (F):	0 to 180
TACK (in.):	5+	LIFT EDGE AVAILABLE:	NO

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

