

319

Double Coated Cloth Tape

Other ITC data sheets are available on our website adhesiveapps.com/our-products

DESCRIPTION

Product 319 is a high strength double coated cloth tape that is based on a durable synthetic cloth carrier with an extremely aggressive synthetic adhesive system. This high performance, highly conformable product offers immediate quickstick yet its dimensional stability allows for removability.

SUGGESTED USES

Product 319 is used for quick and easy tacking of carpet edges, and for carpet installing where removability from various surfaces as wood or cement floors is required. Excellent for use on irregular surfaces for joining, mounting, and laminating where immediate adhesion is desired. **Product 319** also holds mirrors in compacts, mounts printing plates, and is widely used to mount containment barriers during asbestos removal.

SPECIFICATIONS

BACKING: synthetic cloth
ADHESIVE: synthetic copolymer-pigmented-permanent type
LINER: 3.2 mil polysilicone type

THICKNESS, LINER (in.):	.0032	TENSILE STRENGTH	23
THICKNESS, TAPE (in.):	.010	(lb/in.): ELONGATION (%):	10
ADHESION (ozs/in. width):	75	APPLICATION TEMP (F):	35-120
HOLDING POWER (min.):	3,000	TEMPERATURE RANGE (F):	-30 to 140
TACK (in.):	1		

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

