

850

Double Coated Polyethylene Tape

Other ITC data sheets are available on our website adhesiveapps.com/our-products

DESCRIPTION

Product 850 is a double coated polyethylene film tape with our exclusive "Streamline 40" release liner. It is comprised of a 1 mil white polyethylene film that is double coated with an aggressive rubber-base adhesive system.

SUGGESTED USES

Product 850 is recommended for carpet installation and a wide range of industrial applications, where permanency is desirable without the possibility of removal. The thin profile makes **Product 850** very conformable.

SPECIFICATIONS

BACKING: polyethylene film, white; .001"
ADHESIVE: synthetic copolymer, permanent type
LINER: 40 lb. "Streamline 40" polysilicone type

THICKNESS, LINER (in.):	.0025	TENSILE STRENGTH	4
THICKNESS, TAPE (in.):	.003	(lb./in): ELONGATION (%):	100
ADHESION (ozs./in. width):	75	APPLICATION TEMP (F):	60-120
HOLDING POWER (min.):	5,000	TEMPERATURE RANGE (F):	0-150
TACK (in.):	3		

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

