

# A200

## 2 MIL CLEAR ACRYLIC HIGH TEMPERATURE TRANSFER ADHESIVE TAPE

### PRODUCT DESCRIPTION

#### Transfer Adhesive

A200 is a high performance unsupported acrylic transfer tape that features excellent permanent adhesion combined with superior high temperature shear properties. The product is supplied on a 76# polycoated kraft liner with a gloss surface to provide moisture stability as well as faster substrate wet out.

### FEATURES & BENEFITS

- Strong adhesion to metals, glass, and high
- Excellent shear strength
- Superior temperature resistance
- Moisture stable polycoated kraft liner

### PRODUCT CONSTRUCTION



### PRODUCT SPECIFICATIONS

| Test                        | Typical Value     | Typical Value (Metric) | Test Method |
|-----------------------------|-------------------|------------------------|-------------|
| Adhesive Thickness          | 2.00 mils         | 0.051 mm               | PSTC-133    |
| Peel Adhesion               | 50 oz/in          | 13.89 N/25mm           | PSTC-101    |
| Tack                        | 32 oz             | 907 g                  | ASTM D 2979 |
| Shear Adhesion              | 168 hrs @ 2.2 psi | 168 hrs @ 15.2 kPa     | PSTC-107    |
| Minimum Service Temperature | -40 °F            | -40 °C                 |             |
| Maximum Service Temperature | 300 °F            | 149 °C                 |             |

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

### Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street  
Easthampton, MA 01027

413-527-7120 Main  
800-356-3572 Toll Free U.S.

[www.adhesiveapps.com](http://www.adhesiveapps.com)

**Adhesive**  
Applications™

Rev A

10/4/2018

