

# A803

## 3 MIL CLEAR ACRYLIC TRANSFER ADHESIVE TAPE

### PRODUCT DESCRIPTION

#### Transfer Adhesive

A803 is an unsupported permanent acrylic transfer pressure sensitive adhesive that features excellent peel strength and tack. The product is supplied on a 76# polycoated kraft release liner.

### FEATURES & BENEFITS

- High tack, high peel adhesive with moderate
- Strong anchorage to many foam materials
- Excellent moisture resistance
- Able to be applied at low temperatures
- Stabilized with glass fibers for cleaner slitting and die cutting

### PRODUCT CONSTRUCTION



### PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Adhesive Thickness	3.00 mils	0.076 mm	PSTC-133
Peel Adhesion	112 oz/in	31.12 N/25mm	PSTC-101
Tack	42 oz	1191 g	ASTM D 2979
Shear Adhesion	18 hrs @ 2.2 psi	18 hrs @ 15.2 kPa	PSTC-107
Minimum Service Temperature	-40 °F	-40 °C	
Maximum Service Temperature	300 °F	149 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

### Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street  
Easthampton, MA 01027

413-527-7120 Main  
800-356-3572 Toll Free U.S.

[www.adhesiveapps.com](http://www.adhesiveapps.com)

**Adhesive**  
Applications™

Rev A

9/18/2018

