

AT20

2 MIL CLEAR ACRYLIC TRANSFER ADHESIVE TAPE

PRODUCT DESCRIPTION

Transfer Adhesive

AT20 is a high performance glass filled acrylic transfer tape well suited to a wide variety of end uses. A versatile acrylic adhesive, AT20 is an effective solution for general industrial bonding, precision component assembly, and graphic arts applications.

FEATURES & BENEFITS

- High performance transfer tape
- Able to be applied at low temperatures
- Moderate shear strength
- Excellent UV and chemical resistance
- Stabilized with glass fibers for cleaner slitting and die cutting
- Very good adhesion to metals, glass, foams, and high surface energy plastics

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Adhesive Thickness	2.00 mils	0.051 mm	PSTC-133
Peel Adhesion	48 oz/in	13.34 N/25mm	PSTC-101
Tack	35 oz	992 g	ASTM D 2979
Shear Adhesion	48 hrs @ 2.2 psi	48 hrs @ 15.2 kPa	PSTC-107
Minimum Service Temperature	-40 °F	-40 °C	
Maximum Service Temperature	250 °F	121 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

Rev A

9/18/2018

