

AT60

6 MIL CLEAR ACRYLIC TRANSFER ADHESIVE TAPE

PRODUCT DESCRIPTION

Transfer Adhesive

AT60 is a high performance glass filled acrylic transfer tape for use in demanding transfer adhesive applications. The product is well suited for foam fabrication, gasket fabrication, and general industrial applications where a high adhesive thickness is required.

FEATURES & BENEFITS

- High performance transfer tape
- Bonds well to rough or irregular surfaces
- Able to be applied at low temperatures
- Excellent UV and chemical resistance
- Stabilized with glass fibers for cleaner slitting and die cutting
- Very good adhesion to metals, glass, foams, and high surface energy plastics

PRODUCT CONSTRUCTION



PRODUCT SPECIFICATIONS

Test	Typical Value	Typical Value (Metric)	Test Method
Adhesive Thickness	6.00 mils	0.152 mm	PSTC-133
Peel Adhesion	128 oz/in	35.56 N/25mm	PSTC-101
Tack	42 oz	1191 g	ASTM D 2979
Shear Adhesion	6 hrs @ 2.2 psi	6 hrs @ 15.2 kPa	PSTC-107
Minimum Service Temperature	-40 °F	-40 °C	
Maximum Service Temperature	250 °F	121 °C	

Tested values are typical under standard conditions and are not intended to be used for specification development. Technical data is believed to be true and accurate; Adhesive Applications recommends that the purchaser test for performance and fitness of use in all applications.

Adhesive Applications - The Adhesive Solutions Company

41 O'Neill Street
Easthampton, MA 01027

413-527-7120 Main
800-356-3572 Toll Free U.S.

www.adhesiveapps.com

Adhesive
Applications™

Rev A

9/18/2018

